

2

DTIC FILE COPY

AD

TECHNICAL REPORT ARCCB-TR-88001

**THE HIGH PRESSURE SOUND VELOCITY AND
EQUATION OF STATE OF AQUEOUS SOLUTIONS
OF HYDROXYLAMMONIUM NITRATE AND
TRIETHANOLAMMONIUM NITRATE**

AD-A191 740

J. FRANKEL

M. DOXBECK

DTIC
ELECTE
MAR 11 1988
S H D

JANUARY 1988



**US ARMY ARMAMENT RESEARCH,
DEVELOPMENT AND ENGINEERING CENTER
CLOSE COMBAT ARMAMENTS CENTER
BENÉT LABORATORIES
WATERVLIET, N.Y. 12189-4050**



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

98 213

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The use of trade name(s) and/or manufacturer(s) does not constitute an official indorsement or approval.

DESTRUCTION NOTICE

For classified documents, follow the procedures in DoD 5200.22-M, Industrial Security Manual, Section II-19 or DoD 5200.1-R, Information Security Program Regulation, Chapter IX.

For unclassified, limited documents, destroy by any method that will prevent disclosure of contents or reconstruction of the document.

For unclassified, unlimited documents, destroy when the report is no longer needed. Do not return it to the originator.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ARCCB-TR-88001	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) THE HIGH PRESSURE SOUND VELOCITY AND EQUATION OF STATE OF AQUEOUS SOLUTIONS OF HYDROXYLAMMONIUM NITRATE AND TRIETHANOLAMMONIUM NITRATE		5. TYPE OF REPORT & PERIOD COVERED Final
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) J. Frankel and M. Doxbeck		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army ARDEC Benet Laboratories, SMCAR-CCB-TL Watervliet, NY 12189-4050		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS AMCMS No. 611102H60 PRON No. A172026402A11A
11. CONTROLLING OFFICE NAME AND ADDRESS US Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		12. REPORT DATE January 1988
		13. NUMBER OF PAGES 18
14. MONITORING AGENCY NAME & ADDRESS (If different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES Submitted to <u>Journal of Energetic Materials</u> .		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Equation of State, Liquid Propellants Thermodynamic Properties Ultrasonics Liquids		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A cell for high pressure sound velocity measurements of liquids was designed and used in a Birch-Bridgman high pressure system with a liquid propellant specimen. The dependence of the sound velocity on pressure to 4.2 kbar (4200 atmospheres) was measured at room temperature and on temperatures between 220 and 293 K at room pressure. These data, together with the temperature dependence of the specific heat which was also measured and some thermodynamic arguments, were used to obtain the full equation of state with (CONT'D ON REVERSE)		

20. ABSTRACT (CONT'D)

temperature and the pressure dependence of the specific heat and of the volume expansivity at room temperature. We compare our results with data obtained by volumetric and other ultrasonic measurements.

(Signature)

UNCLASSIFIED

TABLE OF CONTENTS

	<u>Page</u>
ACKNOWLEDGEMENTS	ii
INTRODUCTION	1
EXPERIMENTAL DETAILS	4
DATA ANALYSIS AND ROOM TEMPERATURE EQUATION OF STATE	6
DISCUSSION	7
THE FULL PVT THERMODYNAMIC DESCRIPTION OF THE FLUID	8
REFERENCES	11

TABLES

I. LIQUID PROPELLANT COMPOSITIONS	4
II. PRESSURE AND TEMPERATURE DEPENDENCE OF THERMODYNAMIC QUANTITIES	9

LIST OF ILLUSTRATIONS

1. Schematic of the ultrasonic cell.	12
2. Comparison of the pressure dependence of the longitudinal sound velocity with Costantino's data.	13
3. Comparison of the change of density results from our analysis based on sound velocity data and Costantino's volumetric measurements.	14
4. The linear relationship between the bulk modulus $B = V_0(\partial P/\partial V)_T$ and the pressure.	15
5. Curves giving the pressure dependence of the volume at different temperatures resulting from our analysis.	16

Accession For

NTIS GRA&I ☒

DTIC TAB ☐

Unannounced ☐

Justification

By

Distribution/

Availability Codes

Dist

Avail and/or
Special

ACKNOWLEDGEMENTS

The authors wish to thank Mr. W. Korman for technical assistance, Dr. N. Klein and Mr. J. F. Cox for helpful discussions, and Dr. Reza M. Mossadegh for the atmospheric pressure specific heat measurements of our propellant. We would also like to thank Dr. M. Costantino for a prepublication copy of his paper. The authors gratefully acknowledge support from AED, US Army ARDEC, Picatinny Arsenal, New Jersey. We would also like to thank Ellen Fogarty for her exemplary editing and typing.

INTRODUCTION

In the course of its utilization from storage to combustion, the propellant is subjected to intervals of high pressure up to an estimated 50,000 psi (3.4 kbars). We note that the thermodynamic properties which control its use are not only temperature-dependent, but also density-dependent. It is therefore useful to know the equation of state (EOS) as a basis for further study of the pressure dependence of any thermodynamic properties of the material. Density-volume relations may be obtained directly by volume measurements as the pressure is changed isothermally (ref 1), or from the pressure dependence of the sound velocity (ref 2) under isothermal conditions. The sound velocity at our frequencies (≈ 10 MHz) gives adiabatic properties of the material whose thermodynamic state is defined by pressure and temperature. This forces us to distinguish between adiabatic and isothermal pressurizations of a system. In both cases we assume quasistatic, reversible processes, which are idealizations. For the adiabatic case, no heat enters or leaves the system and the temperature is allowed to increase, while for the isothermal case the temperature is constant, but heat is allowed to flow out of the system. The parameters to describe either system have to be adiabatic or isothermal respectively, and these quantities are not the same.

The measurement of sound velocity in a system which is isothermally compressed gives us an adiabatic property (e.g., the compressibility from Eq. (1)) for a state which has been arrived at through isothermal processes. It is

¹M. Costantino, "The High Pressure Equation of State of LGP 1845 and LGP 1846," Proceedings of 1986 JANNAF Propulsion Meeting, CPIA Publication 455, Vol. 1, August 1986, p. 237.

²J. Schroeder, J. Frankel, M. Doxbeck, Y. T. Lee, and K. E. Patton-Hall, "Ultrasonic and Rayleigh-Brillouin Scattering Studies of Aqueous Solutions of Hydroxyl Ammonium Nitrate and Triethanol Ammonium Nitrate," Proceedings of 1986 JANNAF Propulsion Meeting, CPIA Publication 455, Vol. 1, August 1986, p. 247.

therefore necessary to convert the adiabatic property we obtain by measuring the velocity of sound in a state defined by P and T to an isothermal property referred to the same state. The equation which relates the sound velocity $v(T,P)$ to the adiabatic compressibility $K_S(T,P)$, which is defined as $-(1/V)(\partial V/\partial P)_S$ or $\frac{1}{\rho} \left(\frac{\partial \rho}{\partial P}\right)_S$, and the density $\rho(T,P)$ is (in the absence of relaxation effects)

$$\frac{1}{K_S} = \rho v^2 \quad (1)$$

The equation which takes us from an adiabatic to an isothermal description of the state is

$$K_T = K_S + \frac{TV\beta^2}{C_p} \quad (2)$$

Here, K_T is the isothermal compressibility, V is the volume per unit mass ($V = \frac{1}{\rho}$), C_p is the specific heat, T is the temperature in K, and β is the volume expansivity given by $(1/V)(\partial V/\partial T)_P$ or $-(1/\rho)(\partial \rho/\partial T)_P$. From Eqs. (1) and (2) we can get

$$\left(\frac{\partial V}{\partial P}\right)_T = -\frac{TV^2\beta^2}{C_p} - \frac{V^2}{v^2} \quad (3)$$

If Eq. (3) is integrated, a relationship between the change of density and pressure (ref 3) can be obtained at constant temperature T .

$$\rho(P) - \rho(P_0) = \int_{P_0}^P \frac{dP}{v^2} + \int_{P_0}^P \frac{T\beta^2}{C_p} dP \quad (4)$$

The pressure dependence of the sound velocity which is necessary for evaluation of the first integral on the right-hand side is available from our measurement.

³R. K. Cook, "Variation of Elastic Constants and Static Strains with Hydrostatic Pressure: Method for Calculation From Ultrasonic Measurements," Acoust. Soc. Am., Vol. 29, No. 4, April 1957, p. 445.

The pressure dependence of β and C_p can be obtained from thermodynamic considerations:

$$\left(\frac{\partial \beta}{\partial P}\right)_T = - \left(\frac{\partial K_T}{\partial T}\right)_P \quad (5)$$

where

$$K_T(T) = \frac{1}{\rho(T)} \left[\frac{1}{v^2(T)} + \frac{T\beta^2(T)}{C_p(T)} \right] \quad (6)$$

The temperature dependence for each quantity on the right-hand side of Eq. (6) is available for LP 1845. We have $\rho(T)$ or $\beta(T)$ from Messina et al. (ref 4) for LP 1845 and $C_p(T)$ and $v(T)$ from our own measurements for our nominal 1845 mixture (see Table I). If we use Messina's data as appropriate for our mixture

$$\rho(T) - \rho(0^\circ\text{C}) = -0.0007119 T \quad (7)$$

and

$$v(T) = 1966 - 1.703 T \quad (8)$$

where ρ is in gm/cm^3 , T is in $^\circ\text{C}$ between -60 and $+23$, and v is in m/sec . The value of C_p at room temperature is 2.29 joules/ gm°C . Hence, $\left(\frac{\partial K_T}{\partial T}\right)_P$ for Eq. (5) yields $5.2 \times 10^{-6}/^\circ\text{C bar}$. Therefore, the pressure dependence of the volume expansivity for room temperature is given by

$$\beta = 4.898 \times 10^{-4} - 5.20 \times 10^{-6} P \quad (9)$$

in units of K^{-1} . The pressure dependence of the specific heat C_p can be found from (ref 5):

$$\left(\frac{\partial C_p}{\partial P}\right)_T = - T \left(\frac{\partial^2 V}{\partial T^2}\right)_P \quad (10)$$

⁴N. A. Messina, H. H. Tseng, L. S. Ingram, and M. Summerfeld, "The Role of Physical Properties in Dynamic Loading Processes and Bubble Collapse of Liquid Monopropellants for LPG Applications," Proceedings of Twenty-First JANNAF Combustion Meeting, CPIA Publication 412, Vol. II, October 1984, p. 515.

⁵P. W. Bridgman, The Physics of High Pressure, G. Bell and Sons, Ltd., London, 1949.

We have $\rho(T)$ from Eq. (7); V is the specific volume ($= 1/\rho$), and

$$\left(\frac{\partial^2 V}{\partial T^2}\right)_P = -\frac{1}{\rho^2} \left(\frac{\partial^2 \rho}{\partial T^2}\right)_P + \frac{2}{\rho^3} \left(\frac{\partial \rho}{\partial T}\right)_P^2 \quad (11)$$

Therefore, from Eqs. (7), (10), and (11)

$$\left(\frac{\partial C_P}{\partial P}\right)_T = -\frac{2T}{\rho^3} \left(\frac{\partial \rho}{\partial T}\right)_P^2 = -9.78 \times 10^{-6} \text{ joules/gm}^\circ\text{C-bar} \quad (12)$$

$(\partial K_T/\partial T)_P$ in Eq. (5) equals the pressure derivative of the expansivity only in the vicinity of P , the pressure at which $(\partial K_T/\partial T)_P$ is evaluated. In our case, the pressure is P_0 , atmospheric pressure. More generally, for higher P , the pressure dependence of the expansivity should be written as

$$\beta(P) = \beta(P_0) + P\left(\frac{\partial \beta}{\partial P}\right)_{P_0} + \frac{P^2}{2!} \left(\frac{\partial^2 \beta}{\partial P^2}\right)_{P_0} + \dots \quad (13)$$

Here we only use the first two terms of Eq. (13). We assume no great curvature in β , so that $(\partial^2 \beta/\partial P^2)_{P_0} \ll (\partial \beta/\partial P)_{P_0}$. An equation similar to Eq. (13) for $C_P(P)$ would also be correct, and similar arguments would apply, and $\frac{P^2}{2!} \left(\frac{\partial^2 C}{\partial P^2}\right)_{P_0}$ is thought to be much smaller than the retained terms.

EXPERIMENTAL DETAILS

A mixture of hydroxylammonium nitrate (HAN), triethanolammonium nitrate (TEAN), and water was prepared whose composition is given in Table I. Compositions of 1845 and 1846 mixtures are given for comparison.

TABLE I. LIQUID PROPELLANT COMPOSITIONS

	Wt. % HAN	Wt. % TEAN	Wt. % H ₂ O
1845	63.2	19.9	16.8
present	62.3	19.6	18.1
1846	60.8	19.2	20.0

The Birch-Bridgman system was built by the Harwood Corporation.* A high pressure oil was used to transmit pressure to the specimen. The pressure was measured to better than 1.5 percent by means of a manganin coil built in the bottom closure of the high pressure cell. This coil was calibrated by means of another coil which had been calibrated with a dead weight tester.

A cell was designed and built to measure liquid sound velocities in a high pressure environment (Figure 1). This cell was also used to measure the temperature dependence of the sound velocity. It has a threaded right circular cylinder (the buffer), 0.5 inch in diameter, which separates the transducer from the specimen. Faces A and B of the buffer are plane parallel. A 10-MHz lithium niobate transducer is bonded to face A, and face B is in contact with the liquid specimen. Face C of the reflector is parallel to the other two faces and remains at a fixed known distance from face B. For this purpose, the buffer is threaded into the threaded holding ring and the spacer and reflector are pushed up against it by a threaded disk which has a ball-like protrusion in the center. The spacer and the reflector have small openings near their edges which allow the specimen liquid to travel from below the threaded disk to the specimen chamber. The separator membrane seen in Figure 1 serves as a separator and pressure transmitter between the specimen and the pressurizing oil in the Birch-Bridgman cell. The ultrasonic transducer is pulsed with a broadband gated amplifier. Ultrasonic pulses are produced in the buffer, travelling at right angles to faces A and B. As a pulse impinges on B, a part is reflected back to A, and the remaining part travels through the liquid specimen and is reflected back and forth between B and C. After each traverse, again at face B, part of

*Harwood Corporation, Walpole, MA.

the pulse is transmitted and proceeds to face A and is sensed by the transducer. From there it is amplified by a broadband receiver. The amplified signal is displayed on a Tektronix 7704A oscilloscope where the time delay measurements are made to a resolution of about 5 nsec. The sound velocity thus obtained in our mixture to 4.2 kbar at room temperature is shown in Figure 2.

DATA ANALYSIS AND ROOM TEMPERATURE EQUATION OF STATE

We use Eq. (4) to determine density where β and C_p are linear with pressure. The sound velocity in m/sec was fit to pressure (in bars) using a singular value decomposition least squares fit program (refs 6,7), and can be given by

$$v = 1942.79 + 0.154 P - 6.482 \times 10^{-6} P^2 - 1.638 \times 10^{-10} P^3 \quad (14)$$

We measure the velocity with a variance of ~ 2 m/sec. The standard error of estimate of our measurements from Eq. (14) is 4.66 m/sec. In order to evaluate the integrals in Eq. (4) we used Bode's rule.

$$\int_{x_0}^{x_4} f(x) dx = \frac{2h}{45} [7f_0 + 32f_1 + 12f_2 + 32f_3 + 7f_4] \quad (15)$$

For the second integral in Eq. (4), we used the linear pressure dependence of the specific heat. The specific heat at 1 atm. is correct to \pm one percent. This leads to a variance of $\sim 10^{-2}$ J/gm°C in C_p , which leads to a variance in the density of $\sim 10^{-4}$ gm/cm³. Using Eqs. (4), (7), (9), (12), (14), and (15), the room temperature equation of state (Figure 3) was calculated to be:

$$\rho = 1.453 + 2.938 \times 10^{-3} P - 2.171 \times 10^{-9} P^2 + 1.219 \times 10^{-13} P^3 \quad (16)$$

⁶S. E. Koonin, Computational Physics, Benjamin/Cummings Publishing Company, Menlo Park, CA, 1986.

⁷G. Forsythe, M. Malcolm, and C. Moler, Computer Methods for Mathematical Computations, Prentice-Hall, Englewood Cliffs, NJ, 1977.

Figure 4 shows the fit of the EOS data by means of the Tait Equation,
 $B = -V_0 \frac{dP}{dV}$. For the Tait Equation, the fit gives:

$$B = 48.68 + 10.85 P \quad (17)$$

where B (the bulk modulus) and P are in kbar.

DISCUSSION

In Figure 2 we present the results of the sound velocity dependence on pressure. For comparison, we also have Costantino's data for LP 1845, also taken at room temperature, but obtained with volumetric measurements. The comparison indicates a difference which increases systematically with pressure, the values starting initially alike, and then increasing to a difference of about 25 m/sec (one percent) at 4 kbar. From the variance given for both measurements, this difference is acceptable. It is interesting, however, to speculate on other possible reasons. The small difference in composition of our mixture from LP 1845 can not explain the difference since Costantino also measured LP 1846 and our velocity measurements are lower than both of his LP 1845 and 1846 values, even though our composition is between them. The possibility also exists of heating due to adiabatic compression of the specimen (due to heating without any dissipation of heat from the specimen). We consider the specimen mass only. The temperature increase, associated with an adiabatic compression only, is given by $\Delta T = \frac{TV\beta}{C_p} \Delta P$. In our case at room temperature $T = 296$ K, with $V = 0.668$ cm³/gm, $C_p = 229$ Ncm/gmK, $\beta = 4.9 \times 10^{-4}$ K⁻¹, for an adiabatic increase in pressure due to 4000 atmospheres (4.05 N/cm²), the temperature increase is +16 K, i.e., from 23 to 39°C. From our own Eq. (8), we have the temperature coefficient of the velocity at room pressure. If we assume the same temperature coefficient at all pressures, then the drop in velocity due to this temperature increase is about 1.1 percent. This change is of the correct magnitude to

explain the difference, but an attempt was made in our measurement to allow the temperature to stabilize. Data as presented were taken on the up, as well as the down pressure cycle in several runs and no discernible difference was found in the values at high pressure, as well as at zero pressure, before and after the pressure cycling. Each full up and down pressure cycle took about 50 minutes. The equation of state comparison (Figure 3) also shows a difference (which cannot be accounted for by the velocity difference). At 4 kbar our change of density from zero pressure is about 6.2 percent, whereas Costantino's is about 5.0 percent.

This small difference is not surprising, considering that it was arrived at through different physical measurements and calculations, but it would be gratifying to know the reason. We wanted to check the possibility that the increased viscosity of the liquid could alter Eq. (1), and we were unsuccessful in getting a shear wave through the liquid at pressure. We therefore, tentatively conclude that relaxation phenomena are not reflected in the density difference.

THE FULL PVT THERMODYNAMIC DESCRIPTION OF THE FLUID

So far we have obtained the thermodynamic quantities given in Table II. These expressions only hold for the phase regions where the propellant remains a homogeneous mixture of its constituents, where we have no phase changes and no phase separation, and, less stringently, no change in viscosity.

A homogenous isotropic system under hydrostatic pressure obeys the following

$$\frac{dV}{V} = \frac{1}{V} \left(\frac{\partial V}{\partial P} \right)_T dP + \frac{1}{V} \left(\frac{\partial V}{\partial T} \right)_P dT \quad (18)$$

This becomes

$$\int_{V_0}^V \frac{dV}{V} = - \int_{P_0}^{P_1} K_T(P, T_0) dP + \int_{T_0}^{T_1} \beta(P_1, T) dT \quad (19)$$

TABLE II. PRESSURE AND TEMPERATURE DEPENDENCE OF THERMODYNAMIC QUANTITIES*
(Obtained Here)

Equation	Units
$v(T) = 1966 - 1.703T$	m/sec, °C
$K_T(T) = 1.954 \times 10^{-5} + 5.200 \times 10^{-8}T$	bar ⁻¹ , °C
$v(P) = 1942.79 + 0.154P - 6.482 \times 10^{-6}P^2 - 1.638 \times 10^{-10}P^3$	m/sec, bar
$\rho(P) = 1.4532 + 2.9387 \times 10^{-5}P - 2.1711 \times 10^{-9}P^2 + 1.2192 \times 10^{-13}P^3$	gm/cm ³ , bar
$B(P) = 48679 + 10.848P$ (Tait Equation)	bar, bar
$C_p(P) = 2.29 + 9.78 \times 10^{-6}P$	joules/ gm K, bar
$\beta(P) = 4.898 \times 10^{-4} - 5.20 \times 10^{-8}P$	K ⁻¹ , bar
$K_T(P) = 2.02 \times 10^{-5} - 3.38 \times 10^{-9}P + 3.36 \times 10^{-13}P^2$	bar ⁻¹ , bar

*Pressure dependence found at room temperature (23°C).

Temperature dependence found at one atmosphere.

If we know the initial state P_0 , V_0 , T_0 , we can then obtain the equation of state relation at any other $P_1V_1T_1$. In our case, it is convenient to follow the procedure of evaluating the first integral on the RHS from $\rho(P)$ or $K_T(P)$ (both given in Table II) from room pressure P_0 to the desired pressure P_1 , and then use the pressure dependent β obtained from Table II, also in the second integral on the RHS. This integral is evaluated from room temperature to the desired temperature T_1 . A fit to the results of our calculation and data gives us the following relationship for the PVT equation of our fluids under the constraints discussed in this report.

$$\frac{V}{V_0} = \exp[-\{+2.02 \times 10^{-5}P - 1.69 \times 10^{-9}P^2 + 1.12 \times 10^{-13}P^3 - 1.90 \times 10^{-18}P^4\} \\ + 4.898 \times 10^{-4}(T - T_0) - 5.2 \times 10^{-8}P(T - T_0)] \quad (20)$$

Figure 5 also shows several PV curves at different temperatures. We now have a full thermodynamic description of our propellant which is based on the approximations and techniques discussed here. Further equation of state determinations and viscosity measurements with temperature and pressure will be carried out to increase the reliability of these predictions.

REFERENCES

1. M. Costantino, "The High Pressure Equation of State of LGP 1845 and LGP 1846," Proceedings of 1986 JANNAF Propulsion Meeting, CPIA Publication 455, Vol. 1, August 1986, p. 237.
2. J. Schroeder, J. Frankel, M. Doxbeck, Y. T. Lee, and K. E. Patton-Hall, "Ultrasonic and Rayleigh-Brillouin Scattering Studies of Aqueous Solutions of Hydroxyl Ammonium Nitrate and Triethanol Ammonium Nitrate," Proceedings of 1986 JANNAF Propulsion Meeting, CPIA Publication 455, Vol. 1, August 1986, p. 247.
3. R. K. Cook, "Variation of Elastic Constants and Static Strains with Hydrostatic Pressure: Method for Calculation From Ultrasonic Measurements," Acoust. Soc. Am., Vol. 29, No. 4, April 1957, p. 445.
4. N. A. Messina, H. H. Tseng, L. S. Ingram, and M. Summerfeld, "The Role of Physical Properties in Dynamic Loading Processes and Bubble Collapse of Liquid Monopropellants for LPG Applications," Proceedings of Twenty-First JANNAF Combustion Meeting, CPIA Publication 412, Vol. II, October 1984, p. 515.
5. P. W. Bridgman, The Physics of High Pressure, G. Bell and Sons, Ltd., London, 1949.
6. S. E. Koonin, Computational Physics, Benjamin/Cummings Publishing Company, Menlo Park, CA, 1986.
7. G. Forsythe, M. Malcolm, and C. Moler, Computer Methods for Mathematical Computations, Prentice-Hall, Englewood Cliffs, NJ, 1977.




Figure 1. Schematic of the ultrasonic cell.

Comparison of Velocity Data




Figure 2. Comparison of the pressure dependence of the longitudinal sound velocity with Costantino's data.

Comparison of Change in Density Data




Figure 2 Comparison of the change of density measured from

Tait Equation




Figure 4. The linear relationship between the bulk modulus $B = V_0(\partial P/\partial V)_T$ and the pressure.

Complete Equation of State




Figure 5. Curves giving the pressure dependence of the volume at different temperatures resulting from our analysis.

TECHNICAL REPORT INTERNAL DISTRIBUTION LIST

	NO. OF COPIES
CHIEF, DEVELOPMENT ENGINEERING BRANCH	
ATTN: SMCAR-CCB-D	1
-DA	1
-DC	1
-DM	1
-DP	1
-DR	1
-DS (SYSTEMS)	1
CHIEF, ENGINEERING SUPPORT BRANCH	
ATTN: SMCAR-CCB-S	1
-SE	1
CHIEF, RESEARCH BRANCH	
ATTN: SMCAR-CCB-R	2
-R (ELLEN FOGARTY)	1
-RA	1
-RM	1
-RP	1
-RT	1
TECHNICAL LIBRARY	5
ATTN: SMCAR-CCB-TL	
TECHNICAL PUBLICATIONS & EDITING UNIT	2
ATTN: SMCAR-CCB-TL	
DIRECTOR, OPERATIONS DIRECTORATE	1
ATTN: SMCWV-OD	
DIRECTOR, PROCUREMENT DIRECTORATE	1
ATTN: SMCWV-PP	
DIRECTOR, PRODUCT ASSURANCE DIRECTORATE	1
ATTN: SMCWV-QA	

NOTE: PLEASE NOTIFY DIRECTOR, BENET LABORATORIES, ATTN: SMCAR-CCB-TL, OF ANY ADDRESS CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
ASST SEC OF THE ARMY RESEARCH AND DEVELOPMENT ATTN: DEPT FOR SCI AND TECH THE PENTAGON WASHINGTON, D.C. 20310-0103	1	COMMANDER ROCK ISLAND ARSENAL ATTN: SMCRI-ENM ROCK ISLAND, IL 61299-5000	1
ADMINISTRATOR DEFENSE TECHNICAL INFO CENTER ATTN: DTIC-FDAC CAMERON STATION ALEXANDRIA, VA 22304-6145	12	DIRECTOR US ARMY INDUSTRIAL BASE ENGR ACTV ATTN: AMXIB-P ROCK ISLAND, IL 61299-7260	1
COMMANDER US ARMY ARDEC ATTN: SMCAR-AEE	1	COMMANDER US ARMY TANK-AUTMV R&D COMMAND ATTN: AMSTA-DDL (TECH LIB) WARREN, MI 48397-5000	1
SMCAR-AES, BLDG. 321	1	COMMANDER US MILITARY ACADEMY ATTN: DEPARTMENT OF MECHANICS WEST POINT, NY 10996-1792	1
SMCAR-AET-O, BLDG. 351N	1		
SMCAR-CC	1		
SMCAR-CCP-A	1		
SMCAR-FSA	1		
SMCAR-FSM-E	1	US ARMY MISSILE COMMAND REDSTONE SCIENTIFIC INFO CTR ATTN: DOCUMENTS SECT, BLDG. 4484 REDSTONE ARSENAL, AL 35898-5241	2
SMCAR-FSS-D, BLDG. 94	1		
SMCAR-MSI (STINFO)	2		
PICATINNY ARSENAL, NJ 07806-5000			
DIRECTOR US ARMY BALLISTIC RESEARCH LABORATORY ATTN: SLCBR-DD-T, BLDG. 305 ABERDEEN PROVING GROUND, MD 21005-5066	1	COMMANDER US ARMY FGN SCIENCE AND TECH CTR ATTN: DRXST-SD 220 7TH STREET, N.E. CHARLOTTESVILLE, VA 22901	1
DIRECTOR US ARMY MATERIEL SYSTEMS ANALYSIS ACTV ATTN: AMXSY-MP ABERDEEN PROVING GROUND, MD 21005-5071	1	COMMANDER US ARMY LABCOM MATERIALS TECHNOLOGY LAB ATTN: SLCMT-IML (TECH LIB) WATERTOWN, MA 02172-0001	2
COMMANDER HQ, AMCCOM ATTN: AMSMC-IMP-L ROCK ISLAND, IL 61299-6000	1		

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER, US ARMY AMCCOM, ATTN: BENET WEAPONS LABORATORY, SMCAR-CCB-TL, WATERVLIET, NY 12189-4050, OF ANY ADDRESS CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST (CONT'D)

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
COMMANDER US ARMY LABCOM, ISA ATTN: SLCIS-IM-TL 2800 POWDER MILL ROAD ADELPHI, MD 20783-1145	1	COMMANDER AIR FORCE ARMAMENT LABORATORY ATTN: AFATL/MN EGLIN AFB, FL 32543-5434	1
COMMANDER US ARMY RESEARCH OFFICE ATTN: CHIEF, IPO P.O. BOX 12211 RESEARCH TRIANGLE PARK, NC 27709-2211	1	COMMANDER AIR FORCE ARMAMENT LABORATORY ATTN: AFATL/MNG EGLIN AFB, FL 32542-5000	1
DIRECTOR US NAVAL RESEARCH LAB ATTN: DIR, MECH DIV CODE 26-27 (DOC LIB) WASHINGTON, D.C. 20375	1 1	METALS AND CERAMICS INFO CTR BATTELLE COLUMBUS DIVISION 505 KING AVENUE COLUMBUS, OH 43201-2693	1

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER, US ARMY AMCCOM, ATTN: BENET WEAPONS LABORATORY, SMCAR-CCB-TL, WATERVLIET, NY 12189-4050, OF ANY ADDRESS CHANGES.